

# BRIGHTSIGN XT

## STATE-OF-THE-ART TECHNOLOGY AND DOLBY VISION™. ENTERPRISE PERFORMANCE.

BrightSign XT delivers unsurpassed performance for enterprise applications with a powerful 4K video engine, our fastest HTML and graphics engine and our most powerful CPU. This state-of-the-art technology for leading-edge digital signage installations supports H.264 & H.265 decoding, Dolby Vision and HDR10+ media profiles, Full HD and 4K playback including Mosaic Mode. It offers a hardware-accelerated HTML5 rendering engine that enables flawless playback of multiple modular HTML5 assets including Javascript, CSS animations, WebGL and even swipe/gesture interactivity. All XT models offer Gigabit Ethernet, and XT is the only product line offering PoE+ as well as HDMI In for Live TV playback.



### BrightSign XT244

#### Standard I/O Player



Offers our most powerful H.264/H.265 4K & Full HD video engine with Dolby Vision and HDR10+ support, 4K upscaling and dual decoding of two 4Kp60 videos simultaneously. Delivers the best HTML5 rendering performance available for Enterprise applications. Includes the standard I/O package of Gigabit Ethernet with PoE+, GPIO, IR, analog/digital audio and an M.2 SSD PCIe interface.

Price: \$550

### BrightSign XT1144

#### Expanded I/O Player



Includes all the features BrightSign XT244, plus serial, dual USB (type A and C) and Live TV playback via the HDMI 2.0a input to play content from any broadcast channel – even protected HDCP content.

Price: \$650

## Features



H.265



4Kp60 dual decode



Powerful 4K Video Engine



Power over Ethernet



Live TV



Enterprise HTML5



IP Streaming



BrightBeacon™



BrightWall™



AutoWall™



Zones



BrightPlates™



Interactive



Live Feeds



Geo-Fencing



Tagging



BrightSign App



Sign Preview



Remote Snapshot



B-Deploy



IP Streaming Server



Digital Audio



Mosaic Mode



M.2 SSD PCIe Interface

## SPECIFICATIONS

| MODEL   | XT244                        | XT1144                |
|---|------------------------------|-----------------------|
| <b>VIDEO ENGINE DECODER</b>   |                              |                       |
| Native 4K@60p Dolby Vision and HDR10+ video decoding  | X                            | X                     |
| Single video decoding: 4K or 1080p60  | X                            | X                     |
| Dual video decoding: 4K or 1080p60  | X                            | X                     |
| <b>MEDIA FORMATS</b>  |                              |                       |
| Video Codecs for 4K content: H.265/H.264  | X                            | X                     |
| Video Containers for 4K H.265 content: .ts, .mov, .mp4, .mkv  | X                            | X                     |
| Video Codecs for Full HD: H.265, H.264 (MPEG-4 Part 10), MPEG-2   | X                            | X                     |
| Video Containers for Full HD content: .ts, .mpg, .vob, .mov, .mp4, .m2ts, .wmv  | X                            | X                     |
| Image support up to 4K BMP, JPEG, PNG   | X                            | X                     |
| Audio: MP2, MP3, AAC, and WAV (AC3 is passed through)   | X                            | X                     |
| HTML5   | X (Enterprise)               |                       |
| <b>DISPLAY RESOLUTIONS*</b>   |                              |                       |
| 4K resolutions: 4096x2160, 3840x2160, 3840x600  | X                            | X                     |
| Upscaling to: 3840x2160x24/25/29.97/30p   | X                            | X                     |
| 1920x1080, 1920x1200, 1600x1200, 1440x1050, 1440x900, 1360x768, 1280x1024, 1280x960, 1280x800, 1280x768, 1280x720, 1024x768, 800x600, 720x576, 720x480, 640x480 | X                            | X                     |
| <b>HARDWARE INTERFACES</b>  |                              |                       |
| Locking Power Connector   | X                            | X                     |
| External micro SD Slot (SDHC and SDXC); SDHC storage up to 32GB SDXC storage up to 2TB  | X                            | X                     |
| M.2 SSD PCIe Interface  | X                            | X                     |
| USB High Speed Host Port (also supports content updates)  |                              | X (2 ports: Type A&C) |
| 12-pin Phoenix GPIO port with 8 bi-directional GPIOs  | X                            | X                     |
| 3.5mm RS-232 Serial Port  |                              | X                     |
| 3.5mm IR In/Out   | X                            | X                     |
| 3.5mm Audio Out (analog -or- SPDIF digital, non-simultaneous)   | X                            | X                     |
| HDMI 2.0a Out   | X                            | X                     |
| HDMI 2.0a Input   |                              | X                     |
| Ethernet  | X (Gigabit)                  |                       |
| Power over Ethernet (PoE+)  | X                            | X                     |
| M.2 (E) Keyed Wi-Fi/Bluetooth Connector   | X                            | X                     |
| Wi-Fi External Antenna Connector  | X                            | X                     |
| Status LEDs   | Power, Busy, Wireless, Error |                       |
| Reset Button  | X                            | X                     |
| Real Time Clock   | X                            | X                     |
| <b>FEATURES</b>   |                              |                       |
| H.265 Decoding: smaller file sizes and higher quality content than H.264  | X                            | X                     |
| Powerful 4K Video Engine: native 4K Dolby Vision and HDR10+ decoding, 4K upscaling, dual 4K video decoding and superior scaling technologies                    | X                            | X                     |
| Live TV: brings Live TV, even HDCP-protected content, to your signage via HDMI 2.0a Input   |                              | X                     |

| MODEL  | XT244                                       | XT1144                              |
|--|---|-------------------------------------|
| HTML5: hardware-accelerated HTML5 engine plays full screen and modular HTML5 assets up to 4K resolution layered together with high-bandwidth Full HD or 4K video | X (Enterprise)                              |                                     |
| BrightBeacon™: 2-way Bluetooth/Beacon communication between mobile devices & signage (requires: wireless/Bluetooth module)                                       | X   | X                                   |
| BrightWall™: frame-accurate synchronized playback across multiple displays   | X   | X                                   |
| Autowall™: embraces the power of HTML5 to create unique multimedia video walls   | X   | X                                   |
| Zones: playback multiple content types on a single screen  | X   | X                                   |
| Mosaic Mode: play a multitude of smaller resolution videos simultaneously that add up to the maximum video resolution of the player                              | X   | X                                   |
| IP Streaming: play streaming media   | X   | X                                   |
| IP Streaming Server: serve IP streams from local storage   | X   | X                                   |
| Encoding Server: transcode or composite/encode IP streams  | X   | X                                   |
| Interactivity: connect virtually any type of interactive device to a multitude of interactive ports  | X (GPIO, IR, UDP)                           | X (GPIO, dual USB, serial, IR, UDP) |
| Live Feeds: Live Data, Live Text, MRSS, Twitter, Flickr, etc.  | X   | X                                   |
| Tagging: BrightSign Network users can assign media and player tags for highly targeted content distribution  | X   | X                                   |
| BrightSign App: update signs with an iOS device  | X   | X                                   |
| Geo-Fencing: trigger playback based on location (requires USB dongle)  |   | X                                   |
| Sign Preview: preview presentation playback in BrightAuthor  | X   | X                                   |
| Remote Snapshot: remotely view a snapshot image of the display's playback  | X   | X                                   |
| BrightPlates™: easy template-based sign creation service   | X   | X                                   |
| Networking: update, manage and schedule your signage   | X   | X                                   |
| B-deploy: A setup feature to deploy many players at once   | X   | X                                   |
| Extended Thermal: Supports ambient temperatures between 0° & 70° C at 90% max relative humidity, non-condensing  | X   | X                                   |
| <b>SOFTWARE</b>  |   |                                     |
| Free BrightAuthor Software   | X   | X                                   |
| BrightSign Networking Options  | X   | X                                   |
| <b>ACCESSORIES</b>   |   |                                     |
| USB Button Pads  |   | X                                   |
| Wireless/Bluetooth Module  | X   | X                                   |
| MicroSD Class 10 Cards (various capacities)  | X   | X                                   |
| <b>MISCELLANEOUS</b>   |   |                                     |
| Dimensions (W x H x D)   | 179.9 x 21.9 x 204.2mm or 7.1 x 0.86 x 8 in |                                     |
| Weight   | 20 oz                                       |                                     |
| Power  | 12V / 3A (36 Watts)                         |                                     |
| Multi-Country Power & Regulatory Approvals   | X   | X                                   |
| Built-in Wall Mounting Brackets  | X   | X                                   |
| 1 year warranty, parts and labor   | X   | X                                   |